



3)OTIS LG

(3 , 60Hz)

HP		KW	Poles	Frame No.	(100%)										()		
					OTIS LG		380V		440V		380V		440V				
RPM	%	%	A	A	A	A	A	A	%	%							
2	80M	3450	84.0	86.1	1.6	1.4	7.5	6.5	280	H	310	151					
1	0.75	4	80M	1730	84.0	75.5	1.8	1.6	12.1	10.5	250	K	280	147			
	6	90L	1145	84.0	69.6	2.0	1.7	12.1	10.5	250	J	290	152				
	2	90L	3500	86.5	80.7	3.3	2.9	26.0	22.5	240	J	270	130				
2	1.5	4	90L	1730	85.5	78.7	3.4	3.0	25.4	21.9	280	J	330	114			
	6	100L	1140	87.5	73.6	3.6	3.1	17.3	14.9	210	J	230	166				
	2	90L	3500	88.5	87.7	4.4	3.8	38.1	32.9	250	J	280	131				
3	2.2	4	100L	1740	88.5	82.3	4.6	4.0	40.4	34.9	300	J	320	140			
	6	112M	1140	88.5	75.8	5.0	4.3	19.6	16.9	200	J	220	167				
	2	112M	3500	88.5	90.1	7.1	6.2	66.4	57.3	260	K	300	132				
5	3.7	4	112M	1750	89.5	82.8	7.7	6.6	69.3	59.9	290	J	320	115			
	6	132S	1140	88.5	79.2	8.1	7.0	52.0	44.9	220	H	260	133				
	2	132S	3520	88.5	89.8	10.5	9.1	69.3	59.9	180	H	320	141				
7.5	5.5	4	132S	1750	90.2	82.5	11.3	9.8	73.9	63.8	220	H	270	116			
	6	132M	1150	91.0	75.1	12.4	10.7	75.1	64.9	190	H	230	134				
	2	132S	3530	91.0	90.8	13.9	12.0	92.4	79.8	180	H	315	142				
10	7.5	4	132M	1750	91.7	85.5	14.7	12.7	82.0	70.8	210	H	270	117			
	6	160M	1150	91.0	81.4	15.5	13.4	124.1	107.2	224	K	280	124				
	2	160M	3565	91.7	86.4	21.3	18.4	177.6	153.4	252	J	315	143				
15	11	4	160M	1765	92.4	81.8	22.2	19.2	190.6	164.6	244	K	305	119			
	6	160L	1160	91.7	82.4	22.2	19.2	166.5	143.8	208	J	260	125				
	2	160M	3555	91.7	86.4	29.0	25.1	218.7	188.8	240	J	300	144				
20	15	4	160L	1765	93.0	82.8	29.7	25.7	245.2	211.7	214	K	265	120			
	6	180M	1175	93.0	80.6	30.6	26.4	204.4	176.5	223	H	275	126				
	2	160L	3555	92.4	83.2	36.9	31.9	308.3	266.3	264	K	330	145				
25	18.5	4	180M	1770	93.6	86.9	34.7	30.0	267.8	231.2	196	J	245	118			
	6	180L	1175	93.0	78.5	38.7	33.5	298.3	257.6	203	J	250	127				
	2	180M	3550	93.0	87.8	41.3	35.6	325.7	281.3	264	J	330	153				
30	22	4	180M	1770	93.6	86.0	41.7	36.0	359.9	310.8	226	K	280	121			
	6	180L	1175	93.6	81.1	44.6	38.5	311.8	269.3	232	J	290	128				
	2	180L	3550	93.0	89.3	55.3	47.8	456.4	394.1	289	J	360	154				
40	30	4	180L	1770	94.5	85.8	56.6	48.8	512.1	442.3	224	K	280	122			
	6	200L	1170	94.1	79.9	61.0	52.7	477.0	411.9	263	J	325	155				
	2	200L	3555	93.6	89.5	67.7	58.5	650.0	561.4	280	K	350	156				
50	37	4	200L	1765	94.1	87.2	69.0	59.6	548.2	473.4	216	H	270	123			
	6	200L	1170	93.6	83.2	72.5	62.6	535.1	462.1	216	H	270	148				
	2	200L	3545	94.1	91.0	80.2	69.3	691.7	597.4	280	J	350	168				
60	45	4	200L	1760	94.1	85.9	85.0	73.4	627.5	541.9	230	H	285	129			
	6	225S	1175	94.1	82.1	89.0	76.8	624.3	539.2	240	H	300	149				
	2	225S	3550	93.6	92.4	97.0	83.8	905.1	781.6	288	K	335	150				
75	55	4	225S	1760	94.5	83.9	105.9	91.5	750.3	648.0	210	H	260	146			
	6	250S	1180	95.0	83.8	105.5	91.1	678.7	586.2	180	H	225	169				
	2	250S	3550	94.1	92.8	131.2	113.3	1173.5	1013.5	240	J	300	157				
100	75	4	250S	1765	95.4	88.4	136.0	117.5	983.6	849.5	184	H	230	135			
	6	250M	1175	95.0	84.0	143.3	123.7	723.3	624.7	169	H	210	158				
	2	250M	3545	95.0	93.2	155.2	134.1	1200.7	1037.0	267	H	330	170				
120	90	4	250M	1760	95.0	89.9	161.0	139.0	1102.4	952.1	188	H	235	173			
	6	280S	1180	95.4	84.0	171.3	148.0	1220	1054	218	H	238	178				
	2	280S	3545	95.0	93.30	189.4	163.5	1620	1399	216	J	267	171				
150	110	4	280S	1760	95.8	88.60	197.9	170.9	1450	1252	244	H	210	174			
	6	280M	1175	95.4	86.40	203.3	175.6	1285	1110	177	G	228	179				
	2	280M	3545	95.4	93.30	226.5	195.6	1395	1205	112	F	277	172				
175	132	4	280M	1765	95.8	88.50	237.6	205.2	1540	1330	170	G	217	175			
	160	4	315S	1765	95.4	91.54	279.3	241.2	1970	1701	200	H	265	176			
	200	4	315S	1765	95.8	91.60	348.0	300.6	2565	2215	165	H	251	177			

